

**NOTE:** Save these instructions as you may need them at a later date. For your safety, read and understand these instructions completely before starting installation. THIS PRODUCT MUST BE INSTALLED IN ACCORDANCE WITH THE APPLICABLE INSTALLATION CODE BY A PERSON FAMILIAR WITH THE CONSTRUCTION AND OPERATION OF THE PRODUCT AND THE HAZARDS INVOLVED.

**CAUTION:** RISK OF FIRE OR ELECTRIC SHOCK. DISCONNECT MAIN POWER AT FUSE OR CIRCUIT BREAKER BEFORE INSTALLING OR SERVICING THE FIXTURE.

- LED installation requires knowledge of luminaires electrical systems. If not qualified, do not attempt installation contact a qualified electrician.
- Before proceeding with installation, disconnect power to the luminaire. Failure to do so may result in electric shock and lead to injury or death.

### Installation Instructions:

#### Step 1

The E1LDRV60 should be installed into ceiling within 4 feet of the first fixture. Follow the wiring diagram for electrical connections.

#### Step 2

Pass the supply wires through the  $\frac{3}{8}$ " diecast flexible conduit connector.

#### Step 3

Connect black and white supply wires to the input side of terminal block. Ensure the wires are fully inserted into connectors and tighten screws at the top of terminal block.

#### Step 4

Reinstall cover and secure with the included screws.

#### Step 5

Apply AC power, confirm that all fixtures are functioning as expected.

#### NOTE:

Max distance from power supply to last fixture should not exceed 14 feet. \*\*Maximum distance calculation based on 12AWG supply wires.

